



# ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS



## 2007 - 2015 JEEP WRANGLER


PART#: **Z344813-KIT**

### HOOD HINGE LED LIGHT MOUNTS

PARTS ARE PATENT PENDING. ALL RIGHTS RESERVED - COPYRIGHT ©2016 - ZROADZ LED, INC.

## PARTS INCLUDED

- A - (1) ZROADZ LED Combo Left Bracket
- B - (1) ZROADZ LED Combo Right Bracket
- C - (1) ZROADZ Left Side Base Mount
- D - (1) ZROADZ Right Side Base Mount
- E - (2) ZROADZ LED Bracket Legs



## LED LIGHTS INCLUDED

- Z344813-KIT - (1) ZROADZ 20" LED Light Bar
- (2) ZROADZ 6" LED Light Bars

## HARDWARE INCLUDED

- Z344813-KIT**
- (4) - M8 x 35 MM Button Head Allen Cap Screws
  - (4) - M6 x 20 MM Cap Bolts
  - (8) - 1/4" Black Flat Washers
  - (4) - 1/4" Nylon Lock Nuts
  - (4) - 10-32 x 1/2" Button Head Screws
  - (4) - 10-32 Nylon Nuts

## TOOLS REQUIRED

- Socket Set & Ratchet
- Ratchet Extensions
- 7/16 Open Ended Wrench
- 10 MM Open Ended Wrench
- 11 MM Open Ended Wrench
- Various Wrenches
- Allen Key Set

## INSTALLATION GUIDE

### START HERE

PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS BEFORE INSTALLATION. Auto makers offer varied models to each vehicle and occasionally manufacture more than one body style of the same model. To assure your part is correct; our tech department can be contacted at [orders@zroadz.com](mailto:orders@zroadz.com) to verify fitment and assist with technical questions. All other inquires can be directed to [orders@zroadz.com](mailto:orders@zroadz.com). In the event you do not have internet access please call 844-653-8040

\* APPLICATION MODELS VARY. WE RECOMMEND TO VERIFY FITMENT BEFORE BEGINNING INSTALLATION PROCESS.  
\* IMAGES FEATURED IN THE INSTRUCTION DOCUMENTS MAY NOT ALWAYS EXACTLY MATCH YOUR MODEL OR PART.

### BEFORE YOU BEGIN

START HERE: Turn off engine, chalk tires with stop block, open the hood and disconnect the battery.

### LED LIGHT BRACKET INSTALLATION

**STEP 1** 1) Layout and organize the provided parts.



### PRO TIP:

APPLY A PROTECTIVE LAYER OF 3M MASKING TAPE AROUND THE APPLICATION AREA.

### STEP 2

2) Assemble the ZROADZ Base Mounts (C & D) with the ZROADZ Combo Brackets (A & B). Parts can only be assembled one way. Use the (4) - 10-32 x 1/2" Button Head Screws and the (4) - 10-32 Nylon Nuts.

### STEP 3

3) Fit the 20" ZROADZ LED Light Bar to the now assembled ZROADZ Brackets. Use (2) - 1/4" Nylon Lock Nuts and (2) - 1/4" Nylon Lock Nuts.



# ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS

## LED LIGHT BRACKET INSTALLATION - CONTINUED

PARTS ARE PATENT PENDING. ALL RIGHTS RESERVED - COPYRIGHT ©2016 - ZROADZ LED, INC.



FIG 3

### STEP 3

SEE FIGURE 3 & 4

3) Remove the Vehicle's factory bolts from the Hood Hinge Mounts and set aside to be used shortly.



FIG 4

### STEP 4

SEE FIGURES 5 & 6

4) With the LED Light and Bracket Mounts assembled and facing towards the front, carefully move brackets into position and align with the recently exposed factory bolt holes. Secure brackets to Vehicle Hood with the supplied (4) - M8 x 35 MM Button Head Allen Cap Screws. Repeat on other side.




FIG 5

FIG 6

### STEP 5

SEE FIGURE 7

5) Go ahead and use a Allen Key to tighten these screws and secure the ZROADZ Mounting Brackets to the Hood.



FIG 7

### STEP 6

SEE FIGURE 8 & 9

6) It is now time to assemble the (2) 6" LED Lights to the ZROADZ Bracket fixture. Note this is to be done on the Jeep. Do this one side at a time by propping up the LED and using the supplied (2) - 1/4" Nylon Lock Nuts and (2) - 1/4" Nylon Lock Nuts. Tighten down with an open ended wrench.



FIG 8



FIG 9

## LED LIGHT BRACKET INSTALLATION - CONTINUED



# ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS

## LED LIGHT BRACKET INSTALLATION - CONTINUED

PARTS ARE PATENT PENDING. ALL RIGHTS RESERVED - COPYRIGHT ©2016 - ZROADZ LED, INC.



### STEP 7

SEE FIGURE 10 & 11

7) ZROADZ recommends to tighten down the LED Light Bar from the primary front mount but also to tighten down from the rear mount. Use the supplied (4) - M6 x 20 MM Cap Bolts and the (4) - 1/4" Black Flat Washers. Use an open ended wrench.

### STEP 8

SEE FIGURE 5

4) With the LED Lights and Bracket Mounts assembled, take the (2) ZROADZ LED Bracket Legs (Parts E). Carefully remove the mylar cover to expose the double sided tape.

Slip the Bracket Leg on the outside 6" LED Light Mounts and tighten down with the supplied hardware.

### STEP 9

9) ZROADZ recommends LED Lights be wired with ZROADZ harness kit (part# Z390020S-A) or by utilizing a compatible custom wiring harness. Wiring must be installed by competent & knowledgeable automotive electrician.

### STEPS 10

### ADJUSTMENT TIPS

10) To adjust the angle of your Light Bar, rotate the LED(s) to adjust the angles till your desired light pattern is reached. There will be minimal adjustment due to curved light bar orientation. You may than tighten the hardware and secure everything into place. Be careful not to over tighten the mounting hardware.

It is best to adjust the angle with the vehicle on level ground with lights facing a wall, garage door or other solid barrier. We recommend checking from a distance of 25'. Your installation is now completed.

## FINISHED EXAMPLES



## LED LIGHT BRACKET INSTALLATION - PROCESS COMPLETE



# ZROADZ

DYNAMIC LED MOUNTING SOLUTIONS

## ZROADZ PRODUCT WARRANTY

### ZROADZ PRODUCT WARRANTY

ZROADZ warrants its grille products to be free from defects in material and workmanship for the lifetime of the grille. ZROADZ warrants the finish of its grille products for a 3 year period beginning at the time of sale to the end user. These warranties are limited warranties and do not cover abuse, modification or improper installation nor do they cover finish failure caused by caustic cleaning agents, road salts or other chemicals. ZROADZ reserves the right to repair or replace a defective product at its sole discretion. Any ZROADZ product must be returned to ZROADZ for warranty consideration and must be returned at the customer's expense. In the event that the product is deemed to be defective, the repaired or replaced item will be returned via a surface shipping method to the customer at ZROADZ expense. No provision is made for any labor, rental car or other costs incurred by the failure of its products.

## LED LIGHTING EQUIPMENT INSTALLATION / DISCLAIMER

### WARNING

**PLEASE CONSULT YOUR LOCAL AUTOMOTIVE ELECTRICAL PROFESSIONAL FOR INSTALLATION SERVICES AND ADVICE.** ZROADZ IS ONLY EQUIPPED TO PROVIDE BASIC TECHNICAL ASSISTANCE DUE TO THE DIVERSITY OF VEHICLES, VEHICLE OPTIONS & MODIFICATIONS AND LIGHTING CONFIGURATION OPTIONS AVAILABLE. ZROADZ cannot be held liable due to improper component installation and / or faulty wiring.

### GENERAL GUIDELINES

LED Lights & LED Light Bars operate at relatively high currents and should only be installed by qualified personnel with experience in Switched / relayed high draw DC Circuits.

- Light Bars are designed for use only with standard 12v DC power systems
- Light Bars are for OFF-ROAD USE ONLY. Check your local laws & regulations regarding vehicle mounted lights.
- Some Light Bars are equipped with waterproof connectors while others are simply pig-tailed
- Red Wires = POSITIVE | Black Wires = NEGATIVE
- ALWAYS install your lights on a fused circuit. Basic fusing guidelines: maximum 5A for every 10" of LED Light Bar.

### GENERAL USE, INSTALL AND ADJUSTMENT TIPS

NOTE 1: ZROADZ LED Light Bars themselves are for OFF-ROAD USE ONLY.

NOTE 2: Light Bars depending on the configuration of your vehicle and its options and/or modifications may need to be adjusted for appropriate beam projection. To adjust the angle of your light bars simply loosen the mounting hardware on either side of each Light Bar, rotate the Light Bar to adjust the angle, then tighten the hardware once the desired angle is achieved (please be careful not to over-tighten the mounting hardware or scratch the protective powder-coat finish). It is best to adjust the angle with the vehicle on level ground with the lights facing a wall, garage door or other solid barrier at a distance of approximately 25-30 feet.

NOTE 3: Please consult a qualified automotive electrical professional for light bar wiring installation.

NOTE 4: An optional universal wiring harness (part# Z390020S-A) is also available that includes high-heat & oil/fuel resistant wires, waterproof connector, 12v relay, 12v rocker switch, in-line fuse holder. Our universal wiring harness significantly expedites the installation process but is not a vehicles specific "Plug & Play" product and does not eliminate the need for a professional installation.

Please contact your local ZROADZ dealer for more information or visit [www.zroadz.com](http://www.zroadz.com).

## PRODUCT CARE INFORMATION

### PRODUCT CARE INFORMATION

Wash regularly as you would when caring for your vehicles. Never use dish soap. Never leave wet water spots as that may leave a blemish.

### MATTE BLACK FINISH

Paint warranty applies to defects in material and / or workmanship, it does not cover the matte finish surface appearance.

To enjoy the matte appearance for many years to come, please follow these owner care and maintenance tips.

Get a no-shine matte car wash soap that uses no fillers, no silicone, and won't strip your matte paint of its layer of protection.

Do not use wax, detail spray, armorall®, or any products made for normal paint. Use only products specifically developed for matte finish paint. Do not use products that are even mildly abrasive, such as polishes, glazes, or rubbing compounds. Do not use mechanical cleaners or polishers. Do not use terry cloth, cloth, or paper towels. Do not rub the finish vigorously, this will burnish the paint finish, causing a permanent shiny spot. Shiny spots cannot be removed.

Do not use commercial car wash facilities or their shine enhancement products. Most car wash brushes, large mechanized "towels," and shine enhancement products can damage matte paint.

Remove foreign substances such as insect remains, tar, and road debris using a soft applicator and a mild solvent; saturate and soak area before cleaning—rub lightly.

Hand-wash with a soft wash mitt and mild cleaning product safe for matte paint. Use microfiber cleaning cloths with alcohol-based window cleaner for basic surface clean-up.

### GLOSS BLACK FINISH

ZROADZ with Gloss Black Powder Coated Finish may be washed regularly as you would when caring for your vehicles finish using soap and water. ZROADZ should be waxed at the same time that you wax the vehicle. As a general rule, anything you use to clean your vehicles painted surfaces can be used to clean and maintain your ZROADZ grille. A Gloss powder Coated Finish can be cared for in the same fashion that you would care for your vehicles factory paint job. Never leave wet water spots as that may leave a blemish.